

PROFESSIONAL LOUDSPEAKER CONNECTOR

PROFESSIONAL FEMALE LOUDSPEAKER CONNECTOR

For loudspeakers
4 pins
Chassismontage



Ordercode	Model	Dimensions	Prix
CAS001	round	Ø 50mm	3,90
CAS002	rectangular	26 x 30 mm	4,90
CAS003	square	40 x 40 mm	3,90

PROFESSIONAL MALE LOUDSPEAKER CONNECTOR

For loudspeaker
4 pins



Ordercode	Model	Prix
CAS004	female	8,90
CAS101	male	6,90

PROFESSIONAL LOUDSPEAKER ADAPTER

PROFESSIONAL LOUDSPEAKER ADAPTER - FEMALE 4 PINS TO FEMALE 4 PINS

FEMALE 6.35mm MONO JACK TO PROFESSIONAL MALE LOUDSPEAKER ADAPTER

FEMALE 6.35mm MONO JACK TO PROFESSIONAL FEMALE LOUDSPEAKER ADAPTER

FEMALE XLR TO PROFESSIONAL FEMALE LOUDSPEAKER ADAPTER

PROFESSIONAL FEMALE LOUDSPEAKER ADAPTER 4 PINS TO MALE XLR 3 PINS

FEMALE XLR TO PROFESSIONAL MALE LOUDSPEAKER ADAPTER

MALE XLR MONO TO PROFESSIONAL MALE LOUDSPEAKER ADAPTER



CAA49	10,90	CAA52	14,90	CAA53	14,90	CAA54	14,90	CAA55	14,90	CAA56	14,90	CAA57	14,90
-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

LOUDSPEAKER TERMINAL

Ordercode	color	Prix
1 LSTGB	black	3,50
2 LSTGR	red	3,50
3 CM26B	black	6,90
4 CM26R	red	6,90
5 CM13B	black	1,90
6 CM13R	red	1,90
7 CA114B	black	4,90
8 CA114R	red	4,90
9 CA125	black/red	5,90

gold-plated loudspeaker terminal for cable Ø 7 mm



DUAL BANANA PLUG



BANANA PLUGS 4mm



BINDING POST



Binding post safe type



PIEZO HI-FI TWEETERS



No crossover network is required. The excellent transient response provides a pure and clean sound with very low harmonic distortion. Improve the stability of your amplifier by connecting a 33 ohm / 10W resistor in series with the tweeter.

Ordercode	frequency response	sensitivity	Dimensions	Prix
1 PH5	2.5 - 20kHz	91dB	150 x 70 mm	3,90
2 PH6	1.2-23kHz	90dB	190 x 80 mm	4,50
3 PH8	2.5-25kHz	95dB	95 x 95mm	5,50
4 PH9	2-20kHz	90dB	Ø100mm	3,90

DISPATCHING

DISPATCHING POWER CENTRE, 10 CHANNELS + FLASH

each channel protected with fuse, illuminated bipolar switches, flash button (push-button), 15A max. / 3500W max., round (SCHUKO) outlet sockets, dimensions: 19" rack 2U

VDLPC10F 89,90

DISPATCHING POWER CENTRE - 8 CHANNELS

15A max. / 3500W max., rack model, EEC outlet plugs

VDLPC8 49,90

